



GrilleGuy.com, LLC

2004 – 2005 Nissan Titan / Armada Grille Install Instructions

Kit Contents:

Upper kit

3 piece Grille

Vinyl Trim

UV resistant zip ties (14)

Lower kit

1 piece Grille

UV resistant zip ties (4)

Tools Required:

Diagonal cutters

Soldering Iron (optional)

8mm wrench or socket and ratchet (lower only)

Flat blade screwdriver



Upper Installation:



Step 1 – You need to remove the Nissan emblem from the center grille. We used a hot soldering iron to melt the prongs on the backside of the emblem - it was then easily removed.

Step 2 – (optional) For increased airflow, you can remove the solid plastic pieces that are mounted behind the side grilles. These pieces



GrilleGuy.com, LLC

are mounted with clips that can be released by pushing the piece inward until the latches are released. To get it out from behind the grille, you will most likely have to unlatch the top half of the grille frame (the chrome section on this model). These fasteners are undone by twisting the fastener. The grille frame can then be pulled slightly forward to remove the plastic piece out from the top. Having this removed will also make it easier to attach our side grilles. Note: These fasteners look like screws, but they only turn a portion of 1 turn to lock or unlock.

Step 3 – To attach the side grilles – start by routing the zip ties thru the grille, one in each corner. Start by going thru from the backside of the grille - pull until the head of the zip tie is against the back of the grille - then go back thru an adjacent hole. The grille can then be put up to OEM grille and route the zip tie around the a section of the honeycomb and then thru the head of the zip tie and then put the tip thru another hole so that you will be able to pull it from the front. Leave the zip ties loose until you get all four started. Then while aligning the grille gently pull the zip ties to secure the grille. DO NOT over tighten. Using the diagonal cutters carefully cut the excess zip tie, leaving enough so that you can push it back into the hole so you won't see the cut end.

Step 4 – The center grille installation is similar to the sides, except you have the option to place 2 more zip ties along the top and bottom in the center. (from left to right)

Lower Installation:

Step 1 – The underpinning needs to be removed so that the lower grille can be inserted from the bottom. The underpinning is removed using a wrench or socket and ratchet.

Step 2 – Slide the grille from the bottom up behind the lower grille opening.

Step 3 – Using the zip ties as shown, attach the grille to the vertical fins of the OEM grille.





GrilleGuy.com, LLC

Step 4 – Reinstall the underpinning and the installation is complete.



Thanks for purchasing a GrilleGuy.com, LLC grille for your vehicle. If you have any problems, please email Help@Grilleguy.com. This email is reserved for purchasing customers so that we may respond to you quicker. We stand behind our products and want satisfied customers. Word of mouth advertising is priceless! Please feel free to send us pictures of your car or truck once the grille is installed so we can post it in our Gallery section or even use it on our website and/or auctions.